

Application Pipe Material number	Drinking water	Rain-water	Treated water	Heating water	Thermal Solar system	Open cooling water system Steam condensate	Closed cooling water system	Firepoint supply lines	Sprinkler systems	Natural gas installations Liquit gas installations Hydrogen	Fuel oil installations	Industrial applications	Compressed air system	Technical gases					
	NiroSan® 1.4404 AISI 316 L	NiroSan®	NiroSan®	NiroSan®	NiroSan®	NiroSan® Industry	NiroSan®	NiroSan®	NiroSan®	NiroSan® only wet systems	NiroSan® Gas	NiroSan® Industry	NiroSan® Industry	NiroSan® Industry	NiroSan®				
		PURAPRESS®	PURAPRESS®	PURAPRESS®	PURAPRESS®			PURAPRESS®	NiroSan® Industry only dry systems	NiroSan® Industry only dry systems									
NiroSan®-F 1.4521 AISI 443/444	NiroSan®	NiroSan®-F	NiroSan®	NiroSan®	NiroSan® Industry	NiroSan®	NiroSan®	NiroSan®			NiroSan® Industry	NiroSan® Industry	NiroSan® Industry	NiroSan®					
	PURAPRESS® d ≤ 45 mm	PURAPRESS®	PURAPRESS®	PURAPRESS®			PURAPRESS®	PURAPRESS® only wet systems											
NiroSan®-ECO 1.4404 AISI 316 L	NiroSan®	NiroSan®	NiroSan®	NiroSan®	NiroSan® Industry	NiroSan®	NiroSan®				NiroSan® Industry	NiroSan® Industry	NiroSan® Industry	NiroSan®					
	PURAPRESS®	PURAPRESS®	PURAPRESS®	PURAPRESS®			PURAPRESS®												
NiroTherm® 1.4301 AISI 304		NiroSan®	NiroSan®	NiroSan®	NiroSan® Industry	NiroSan®	NiroSan®				NiroSan® Industry	NiroSan® Industry	NiroSan® Industry	NiroSan®					
		NiroTherm®	NiroTherm®	NiroTherm®			NiroTherm®	NiroTherm®								NiroTherm® Industry	NiroTherm® Industry	NiroTherm® Industry	NiroTherm®
				SANHA®-Therm			NiroTherm® Industry	NiroTherm®	SANHA®-Therm										
Dickwandige Stahlrohre 10255, EN 10220 / 10216-1 or EN 10217-1				SANHA®- Heavy Steel Press			SANHA®- Heavy Steel Press				SANHA®- Heavy Steel Press Gas	SANHA®- Heavy Steel Press Gas	SANHA®- Heavy Steel Press Gas	SANHA®- Heavy Steel Press Gas					
SANHA®-Therm C-Stahl 1.0034				SANHA®-Therm	SANHA®-Therm Industry		SANHA®-Therm	SANHA®-Therm				SANHA®-Therm Industry	SANHA®-Therm Industry dry, oil content ≤ 25 mg/m³						
SANHA®-Therm DZ Carbon steel 1.0034 galvanised (inside / outside)							SANHA®-Therm						SANHA®-Therm Industry dry, oil content ≤ 25 mg/m³						
Copper EN 1057/ DVGW-GW 392	SANHA®-Press	SANHA®-Press	SANHA®-Press	SANHA®-Press	SANHA®-Press Solar	SANHA®-Press	SANHA®-Press	SANHA®-Press		SANHA®-Press Gas	SANHA®-Press Solar	SANHA®-Press	SANHA®-Press Solar	SANHA®-Press Gas					
	PURAPRESS®	PURAPRESS®	PURAPRESS®	PURAPRESS®			PURAPRESS®	PURAPRESS® only wet systems											
MultiFit®-Flex PE-RT; Al; PE-RT	3fit®-Press	3fit®-Press	3fit®-Press	3fit®-Press			3fit®-Press					3fit®-Press	3fit®-Press	3fit®-Press					
	3fit®-Push	3fit®-Push	3fit®-Push	3fit®-Push			3fit®-Push					3fit®-Push	3fit®-Push up to compressed air class 5	3fit®-Push					
MultiFit®-PEX PE-Xc				3fit®-Press			3fit®-Press												
				3fit®-Push			3fit®-Push												

recommended
 on demand only
 not suitable

Please pay particular attention to our technical documentation and installation instructions!

Customer support: If you have technical questions or questions concerning the areas of application, please contact us at webuk@sanha.com or 01628 819245